


Datasheet #89089702



The LDALI-PD1 module enables the control of phase-cut dimmed consumers via a DALI channel. Typical application scenarios are the integration of 230V LED-retrofit-bulbs or halogen lamps in DALI lighting applications.

The device supports a wide voltage range from 220-240 VA C 50/60Hz. The LDALI-PD1 is suitable for loads from 1VA up to 75VA. The load type (RL/RC) is automatically detected and used to select a suitable dimming-method (leading or trailing edge phase-cut). The dimming range is 3%-100%.

The integration of the module in the DALI network follows the same simple steps as the integration of a DALI lamp. The device supports the DALI-specification IEC 62386-205 (Device Type 4, "Incandescent lamp"). The LDALI-PD1 modules are directly connected to a DALI-channel and also supplied with energy by that channel. Thus in case of a system failure the intended state of the output is off.

The LDALI-PD1 is equipped with an open-circuit detection that indicates a lamp failure if no load is connected.


The LDALI-PD1 is designed for installation in distribution boxes or behind standard plugs in installation boxes.

Features

- Easy integration into LOYTEC L-DALI lighting system and LROC-40x room automation controllers
- Device configuration with the free LINX Configurator or via the built-in web server of the L-DALI controller
- Dimmable built-in phase-cut dimmer
- Automatic load detection and selection of leading or trailing edge phase-cut dimming
- Suitable for phase-cut dimmed consumers like dimmable retrofit LED and CFL lamps, halogen lamps, ...
- Wide range voltage support (220-240 V AC 50/60Hz)
- Up to 64 LDALI-PD1 modules per DALI channel with sufficient dimensioned bus supply
- Supplied via DALI channel
- Electrically isolated between DALI and mains
- Open circuit detection
- DALI specification IEC 62386-102 and IEC 62386-205 supported
- Firmware update via DALI

L-DALI Phase-Cut Dimmer Module

LDALI-PD1




Specifications	
Type	LDALI-PD1
Dimensions (mm)	51 x 41 x 21 (L x W x H), DIM042
Power supply	DALI bus, idle 3 mA (@16 V DC), typ. 6 mA (@16 V DC), max. 11mA (inrush current)
Voltage	220-240 V AC, 50/60Hz
Operating conditions	0°C – 50°C, 10 – 90% RH, non-condensing, degree of protection: IP20
Interfaces	1 x DALI, protected against overvoltage (mains)
DALI protocol conformance (IEC 62386 parts)	101 ed2, 102 ed2, 205 ed1
Terminal blocks	Push terminals
Connection wires profile	0.2 – 1.5 mm ² [AWG 24 – 12]
Wire stripping length	8 mm [0.31 in]
Load range	1 VA – 75 VA (RC, RL, RLC)*
Maximum wire length to luminaire	25 m
For use with	LDALI-3E10x, LDALI-ME20x, LDALI-PLCx, LROC-40x, LIOB-591

* Note: LED/CFL lamps up to a rated power of 25W may have a power factor of 0.5 only.

Resource limits	
Number of LDALI-PD1	64 per DALI channel, with sufficient dimensioned DALI bus power supply
Order number	Product description
LDALI-PD1	DALI phase-cut dimmer module

Dimensions of the devices in mm and [inch]

DIM042 LDALI-PD1



The products of LOYTEC electronics GmbH are subject to constant development. Therefore, LOYTEC reserves the right to modify technical specifications at any time without prior notice. The most recent datasheet can be downloaded from www.loytec.com.